

# BAMBOO - 198

<b>WEIGHT</b>	550 gr/sqm $\pm$ 10%
<b>THICKNESS</b>	1,1 mm $\pm$ 10%
<b>WIDTH</b>	140 cm $\pm$ 2 cm
<b>COMPOSITION</b>	
<b>TEXTILE</b>	<b>GRS POLYESTER 20% <math>\pm</math> 2%</b>
	<b>GRS COTTON 16% <math>\pm</math> 2%</b>
<b>COATING</b>	<b>POLYURETHANE 40% <math>\pm</math> 2%</b>
	<b>BAMBOO BIOMASS * 24% <math>\pm</math> 2%</b>

\* Bamboo Biomass contained in one running meter saved **255,5 g of CO<sub>2</sub>**.

## TECHNICAL CHARACTERISTICS

<b>TENSILE STRENGTH (ALONG)</b>	>550	N/5cm	ISO 1421
<b>TENSILE STRENGTH (ACROSS)</b>	>600	N/5cm	ISO 1421
<b>MAX. ELONGATION (ALONG)</b>	>15	%	ISO 1421
<b>MAX. ELONGATION (ACROSS)</b>	>25	%	ISO 1421
<b>TEAR STRENGTH (ALONG)</b>	>15	N	ISO 4674-1
<b>TEAR STRENGTH (ACROSS)</b>	>15	N	ISO 4674-1
<b>ADHESION (ALONG)</b>	>30	N/5cm	ISO 2411
<b>ADHESION (ACROSS)</b>	>30	N/5cm	ISO 2411

CARE INSTRUCTIONS



**MABEL** confirms that all the articles with Bamboo Biomass, comply with **REACH** regulations and are **PVC free**.

This article is a product with a high content of natural biomass. Above mentioned values are intended as indicative. Differences of color and tone between batches, as well as small defects of the surface are proof of the product being natural. All orders involve acceptance of the above mentioned tolerance. Customers are warmly invited to test the performances of the material for their specific application, because being it sustainable for various applications, we may have not previously carried out specific tests. We therefore decline any responsibility for improper use of the material itself.