

BAMBOOLINA

WEIGHT	510 gr/sqm \pm 10%
THICKNESS	0,8 mm \pm 10%
WIDTH	140 cm \pm 2 cm
COMPOSITION	
TEXTILE	BAMBOO FABRIC 47% \pm 2%
COATING	POLYURETHANE 35% \pm 2%
	BAMBOO BIOMASS * 18% \pm 2%

* Bamboo Biomass contained in one running meter saved **157,5 g of CO₂**.

TECHNICAL CHARACTERISTICS

TENSILE STRENGTH (ALONG)	>400	N/5cm	ISO 1421
TENSILE STRENGTH (ACROSS)	>400	N/5cm	ISO 1421
MAX. ELONGATION (ALONG)	>100	%	ISO 1421
MAX. ELONGATION (ACROSS)	>120	%	ISO 1421
TEAR STRENGTH (ALONG)	>20	N	ISO 4674-1
TEAR STRENGTH (ACROSS)	>15	N	ISO 4674-1
ADHESION (ALONG)	>25	N/5cm	ISO 2411
ADHESION (ACROSS)	>25	N/5cm	ISO 2411

CARE INSTRUCTIONS



MABEL confirms that all the articles with Bamboo Biomass, comply with **REACH** regulations and are **PVC free**.

This article is a product with a high content of natural biomass. Above mentioned values are intended as indicative. Differences of color and tone between batches, as well as small defects of the surface are proof of the product being natural. All orders involve acceptance of the above mentioned tolerance. Customers are warmly invited to test the performances of the material for their specific application, because being it sustainable for various applications, we may have not previously carried out specific tests. We therefore decline any responsibility for improper use of the material itself.